



HANSON RIVET

& SUPPLY CO.

13241 Weidner Street
Pacoima, CA 91331

Phone: 818-485-0500

FAX: 818-485-0540

Outside CA: 1-800-RRRIVET

www.hansonrivet.com



NG4 AIR-HYDRAULIC TOOL



Genesis® nG4 Hydro Pneumatic Tool

71234 series with fixed stem collector bottle

Features

- Lightweight tool
- Toughened plastic body and heavy duty rubber base
- Vacuum air supply cut-off on trigger
- Enhanced tool life
- Soft touch rubber grip on handle
- Integral cycle counter

Benefits

- Reduces operator fatigue
- High placement speed
- Robust tool
- Minimized air consumption
- Places a wide range of lockbolts & breakstem fasteners
- Ergonomic

Specifications

| | |
|---------------------------|----------------------|
| Weight (min. with equip.) | 2.3 kg (5.1 lbs) |
| Pull force @ 5.5 bar | 18.68 kN (4200 lbf) |
| Stroke (min.) | 17 mm (0.67 in) |
| Cycle time (approx.) | 1.2 sec |
| Air supply pressure | 5-7 bar (80-100 psi) |
| Free air volume @ 5.5 bar | 4.3 litres |
| Noise level | <75 dB(A) |
| Vibration | <2.5m/s ² |

Placing Capability

Up to 6.4mm (1/4") breakstem rivets produced by Avdel except Monobolt® and Interlock® structural rivets.

Can also place:

Avseal® II sealing plugs up to 12 mm

Avtainer® lockbolts 10.0 mm (3/8")

Avdelok® and Maxlok® lockbolts 4.8 mm (3/16") and 6.4 mm (1/4")

Hemlok® structural rivets 6.4 mm (1/4")

Avibulb® XT and Avinox® XT structural rivets



Dimensions (mm)

