

**HANSON RIVET****& SUPPLY CO.**
13241 Weidner Street
Pacoima, CA 91331

Phone: 818-485-0500

FAX: 818-485-0540

Outside CA: 1-800-RRRIVET

www.hansonrivet.com**PROSET XT3 BLIND RIVET TOOL (76003-00003)****For 3/16" & 1/4" Diameter Blind rivets & Lock Bolts**

The ProSet XT3 can be used in a variety of applications, setting a large range of rivets and lock bolts. The extremely long stroke of 1.025" allows the placement of longer rivets like Monobolt and Interlock typically in one stroke. The new ergonomic design ensures comfort and efficiency, the robust tool rubber base is designed to avoid damage and the latest technology lip seals maximise re-priming intervals.

Capacity: Up to 1/4" in all materials standard, structural & closed end blind rivets.**Will also set Lock bolts up to 3/16" (Nose Assembly sold separately).****Weight: 4.72 lbs. Pulling Force: 3,822 lbs. Stroke: 1.02".****Nose Pieces included: 3/16" & 1/4".**

Nosepieces	Part Number
3/16" Open End Rivets	PRN-614
3/16" Closed End / Steel Mandrel	PRN-624
3/16" Closed End / Aluminum Mandrel	PRN-634
3/16" T-Rivets	PRN-625
1/4" Open End Rivets	PRN-811
1/4" Closed End / Steel Mandrel	PRN-822
1/4" T-Rivets	PRN-825

Replacement Jaws	Part Number
3/16" Open End Rivets	PRG540-46
1/4" Open End Rivets	PRG540-44

Jaw Pushers	Part number
For Standard Rivets	DPN276-006
For Structural Rivets	FAN-064

Nose Assemblies for Lock Bolt			
Diameter	Brand	Part Number	Length
3/16"	AVDELOK	76004-15700	4.2"
1/4"	AVDELOK	764004-15800	4.2"
3/16"	MAXLOK	76004-15300	2.6"
3/16"	MAXLOK	76004-15100	4.2"
1/4"	MAXLOK	764004-15400	2.6"
1/4"	MAXLOK	764004-15200	4.2"

Rivet Type	Riveting Capacity	
	Rivet Sizes in inches (mm)	
	3/16 (4,8)	1/4 (6,4)
Open End	●	● **
Closed End	●	● **
HR	●	●
HS		●
Multi-Grip	● **	
TL	●	
T-Rivet	●	●
Self-Pluggers	●	●
Avex	●	●
Stavex	●	●(1)(2)
Avinox / Avibulb	●	
Bulbex	●	
T-Loc	●	
Avdel SR	●	●
Q-Rivet	●	●
Avdelmate	●	●
Avdelok	● (2)	● (2)
Maxlok	● (2)	● (2)

Additional Information
Available online:

[Service Manual](#)[Accessories Manual](#)[Nose Equipment Manual](#)

(**) Use PRG540-46 Jaws.

(1) Non-standard nose piece required.

(2) Non-standard nose equipment required.