



HANSON RIVET & SUPPLY CO.

13241 Weidner Street
Pacoima, CA 91331

Phone: 818-485-0500

FAX: 818-485-0540

Outside CA: 1-800-RRRIVET

www.hansonrivet.com



PNEUMATIC RIVET SQUEEZERS



HAND HELD "C" STYLE RIVET SQUEEZERS



HAND HELD ALLIGATOR STYLE RIVET SQUEEZERS

MODEL	STANDARD YOKES*		RIVET DIAMETER CAPACITIES			APPROXIMATE RIVET LENGTH CAPACITY
	REACH	GAP	SOLID ALUMINUM	SOLID STEEL	TUBULAR STEEL	
3000C	1.5"	1.25"	1/8"	3/32"	3/16"	.250"
	2.0"	1.50"				.500"
	2.5"	1.50"				.500"
	3.0"	1.50"				.500"
6000C	4.0"	1.75"	3/16"	5/32"	1/4"	.750"
	4.5"	1.75"				.750"
	5.0"	1.75"				.750"
	6.0"	1.75"				.750"
9000C	1.5"	1.25"	1/4"	3/16"	5/16"	.250"
	3.0"	1.50"				.500"
	3.5"	1.50"				.500"
	4.5"	1.5"				.500"

MODEL	STANDARD YOKES*		RIVET DIAMETER CAPACITIES			APPROXIMATE RIVET LENGTH CAPACITY
	REACH	CLOSED GAP	SOLID ALUMINUM	SOLID STEEL	TUBULAR STEEL	
3000A	1.50"	.875"	5/32"	1/8"	3/16"	.625"
	2.25"	1.12"	1/8"	3/32"	5/32"	.870"
	3.00"	.937"	3/32"	1/16"	1/8"	.687"
6000A	1.50"	.875"	7/32"	3/16"	1/4"	.625"
	2.25"	1.12"	3/16"	5/32"	3/16"	.870"
	3.00"	.937"	5/32"	9/64"	3/16"	.687"
	3.50"	1.00"	5/32"	1/8"	9/64"	.750"
9000A	1.50"	.875"	1/4"	3/16"	5/16"	.625"
	2.25"		3/16"	5/32"	1/4"	
	3.00"		3/16"	5/32"	3/16"	



HEAVY DUTY HAND HELD "C" STYLE RIVET SQUEEZERS



HEAVY DUTY HAND HELD ALLIGATOR STYLE RIVET SQUEEZERS

MODEL	STANDARD YOKES*		RIVET DIAMETER CAPACITIES			APPROXIMATE RIVET LENGTH CAPACITY
	REACH	GAP	SOLID ALUMINUM	SOLID STEEL	TUBULAR STEEL	
CP-0351 FUDEL	2.1"	1.50"	1/4"	7/32"	3/8"	.250"

MODEL	STANDARD YOKES*		RIVET DIAMETER CAPACITIES			APPROXIMATE RIVET LENGTH CAPACITY
	REACH	GAP	SOLID ALUMINUM	SOLID STEEL	TUBULAR STEEL	
CP-0351 ESVEL	9.12"	2.12"	3/16"	5/32"	1/4"	3/4"

Pedestal available please visit www.hansonrivet.com.



KIT C

HAND HELD "C" STYLE THREADED HARDWARE INSTALLATION TOOL

HARDWARE INSTALLATION KITS FOR STATIONARY TOOLS

KIT A



KIT B



For installing Press-In Threaded Hardware: Nuts, Studs, Inserts, Stand Offs

MODEL	STANDARD YOKES*		RIVET DIAMETER CAPACITIES			APPROXIMATE RIVET LENGTH CAPACITY
	REACH	GAP	SOLID ALUMINUM	SOLID STEEL	TUBULAR STEEL	
6000CHP KIT	3"	1.75"	3/16"	5/32"	1/4"	.750"

KIT	THE TOOLS THESE KITS ARE DESIGNED TO WORK IN (See page C84)	HARDWARE SIZE RANGE
A	6000CS (Adapter Required) 8000CSA & 15KCSA	#2 thru #10 up to 1/2" Long
B	6000CS 8000CSA & 15KCSA	#2 thru 5/16 up to 1-1/4" Long
C	6000C, 6000CS & 6000CHP 8000CSA & 15KCSA	#2 thru #10 up to 1/2" Long

This tool is designed for the installation of Press-In Threaded Hardware such as Nuts, Studs, Inserts, Stand Offs, and Rivets. Tooling Kit "C" is included with this tool.

See page D82-D83 for Squeezer Dies to fit these tools. *NOTE: Other size Yokes available, call for details.



PNEUMATIC RIVET SQUEEZERS



HAND HELD "C" STYLE RIVET SQUEEZER with REMOTE INTENSIFIER



MODEL	STANDARD YOKES		SQUEEZE FORCE (lbf)	RIVET DIAMETER CAPACITIES		
	REACH	GAP		SOLID ALUMINUM	SOLID STEEL	TUBULAR STEEL
NXS-C4K1.5 NXS-C4K3 NXS-C4K4	1.50" 3.00" 4.00"	1.50" 1.50" 1.50"	3,600	1/8"	3/32"	3/16"
NXS-C6K2 NXS-C6K3 NXS-C6K4	2.00" 3.00" 4.00"	1.50" 1.50" 1.50"	6,445	3/16"	5/32"	1/4"
NXS-C9K2 NXS-C9K3 NXS-C9K4	2.00" 3.00" 4.00"	1.25" 1.50" 1.50"	8,790	1/4"	3/16"	5/16"

HAND HELD ALLIGATOR STYLE RIVET SQUEEZER with REMOTE INTENSIFIER



MODEL	STANDARD YOKES		SQUEEZE FORCE (lbf)	RIVET DIAMETER CAPACITIES		
	REACH	CLOSED GAP AT END OF YOKE		SOLID ALUMINUM	SOLID STEEL	TUBULAR STEEL
NXS-A6	6.00"	1.38"	10,100	9/32"	1/4"	5/16"
NXS-A8	8.00"	1.38"	7,862	1/4"	3/16"	5/16"
NXS-A10	10.00"	1.38"	6,416	7/32"	3/16"	1/4"



Shown with optional Pedestal.