



HANSON RIVET®
 & SUPPLY CO.
 13241 Weidner Street
 Pacoima, CA 91331

Phone: 818-485-0500

FAX: 818-485-0540

Outside CA: 1-800-RRRIVET

www.hansonrivet.com



ACCUBIRD PRO CORDLESS BLIND RIVET TOOL



ACCUBIRD PRO

The brushless motor and high pulling force makes this tool extremely fast and reliable.

Capacity: up to 3/16" diameter:
 standard open end blind rivets in all materials.
 Weight: 4.63 lbs. Pulling Force: 2697 lbs. Stroke: .984"
 Nose Pieces Included: 3/32", 1/8", 5/32 & 3/16"

Battery life: 500 to 1,800 rivets per charge,
 depending on size & material.

Complete with carrying case battery & charger.

The Cordless Alliance System (CAS) is a cross-manufacturer battery pack system of leading power tool brands.

TOOL CAPACITY

RIVET MATERIAL		RIVET DIAMETERS			
		STANDARD COMMERCIAL OPEN-END RIVETS			
BODY	MANDREL	3/32	1/8	5/32	3/16
ALUMINUM	ALUMINUM	●	●	●	●
ALUMINUM	STEEL	●	●	●	●
STEEL	STEEL	●	●	●	●
STAINLESS	STEEL	●	●	●	●
STAINLESS	STAINLESS	●	●	●	●

STANDARD NOSEPIECES

TYPE OF RIVET	RIVET DIAMETER	NOSEPIECE
OPEN-END RIVET	3/32	RTP-1434976
	1/8	RTP-1434955
	5/32	RTP-1434973
	3/16	RTP-1434975

SPECIAL LONG NOSEPIECES *

RIVET DIAMETER	PART NUMBER	"A" SHANK LENGTH	"B" SHANK DIA.
3/32"	RTP-1457367	.590	.236
1/8"	RTP-1457370	.590	.236
5/32"	RTP-1457374	.590	.314
3/16"	RTP-1457385	.590	.393

*Long nosepieces may require special long mandrels

** Other lengths are available - please call for more information

APPROXIMATE RIVETS PER CHARGE

RIVET BODY DIAMETER	MATERIAL	RIVETS/CHARGE
3/32	ALUMINUM	1,800
1/8	ALUMINUM	1,100
1/8	STEEL	1,100
1/8	STAINLESS	1,100
5/32	ALUMINUM	1,100
5/32	STEEL	1,000
5/32	STAINLESS	950
3/16	ALUMINUM	850
3/16	STEEL	1,000
3/16	STAINLESS	700

RETAINING NOSEPIECES

RIVET DIAMETER	PART NUMBER	RECOMENDED MANDREL DIAMETER
3/32"	RTP-1655422	.072
1/8"	RTP-1655422	.095
5/32"	RTP-1655428	.106
3/16"	RTP-165 5430	.126

ADDITIONAL SIZES AVAILABLE

PRO SERIES CAS REPLACEMENT BATTERIES & CHARGER

Battery Part Number	Battery Specification	Charger Part number	Charger Specification
RTP-1679689	18V 2AH Li-Ion	RTP-1679696	18V Li-Ion
RTP-1679690	18V 4AH Li-Ion		